# **Operator's Manual**



**Rigid Dump Truck** 

Serial No. EH5000ACII EH5000ACII

411RD: 77706 and Up 8RAAA: 8RAAAN00001000 and Up



#### INTRODUCTION

**Read this manual** carefully to learn how to operate and service your rigid dump truck correctly. Failure to do so could result in personal injury and/or rigid dump truck damage.

This manual should be considered a permanent part of your rigid dump truck and should remain with the rigid dump truck when you sell it.

**Measurements** in this manual are given in both metric and customary U.S. unit equivalent. Use only correct replacement parts and fasteners. Metric and inch fasteners may require a specific metric or inch wrench.

Write product identification numbers in the Rigid dump truck Numbers section. Accurately record all the numbers to help in tracing the rigid dump truck should it be stolen. Your dealer also needs these numbers when you order parts. File a copy of the identification numbers in a secure place off the rigid dump truck.

**Warranty** is provided as a part of Hitachi's support program for customers who operate and maintain their equipment as described in this manual. The warranty is explained on the warranty certificate which you should have received from your dealer.

This warranty provides you the assurance that Hitachi will back its products when defects occur within the warranty period. In some circumstances, Hitachi also provides field improvements, often without charge to the customer, even if the product is out of warranty. Should the equipment be abused or modified to change its performance beyond the original factory specifications, the warranty will become void and field improvements may be denied.

Setting fuel delivery above specifications or otherwise overpowering rigid dump trucks will result in such action.

Moreover, when replacement parts are required, be sure to use genuine Hitachi parts. Failure to do so may result in voiding the warranty and/or denial of field improvements.

Only qualified, experienced operators officially licensed (according to local law) should be allowed to operate the rigid dump truck.

Only officially, licensed personnel should be allowed to inspect/service the rigid dump truck.

The Yellow Pages in this operator's manual contain IMPORTANT SAFETY INFORMATION.

Read these pages thoroughly and familiarize yourself with the safety standards and recommendations set forth in these yellow pages of the manual.

Follow all safety instructions prior to and while operating the rigid dump truck.

Prior to operating this rigid dump truck, it may be necessary to make modifications to it so that it complies with the local standards (including safety standards) and requirements of your country. Please do not operate this rigid dump truck until such compliance has been confirmed. Please contact Hitachi Construction Truck Manufacturing Ltd. or any of our authorized dealers concerning compliance.



	INTRODUCTION	
(Blank)		

# INDEX

**MACHINE NUMBERS** 

**SAFETY** 

SAFETY SIGNS

**COMPONENTS NAME** 

**OPERATOR'S STATION** 

**BREAK-IN** 

**OPERATING THE RIGID DUMP TRUCK** 

**OPERATING METHODS** 

TRANSPORTING

MAINTENANCE

**STORAGE** 

**TROUBLESHOOTING** 

**SPECIFICATIONS** 

**OPTIONS** 

INFORMATION FEEDBACK FORM

**ALPHABETICAL INDEX** 

INTRODUCTION	DISCHARGE ACCUMULATORS HANDLE FLUIDS SAFELY AVOID FIRES.	
INDEX	A FEW SIMPLE RULES WHEN SERVICING	
	USE TOOLS PROPERLY	
MACHINE NUMBERS	PREVENT BURNS	
RIGID DUMP TRUCK TYPE AND	REPLACE RUBBER HOSES	
SERIAL NUMBERM-1	PERIODICALLY	. S-21
ROLLOVER PROTECTIVE STRUCTURE	AVOID HIGH-PRESSURE FLUIDS	. S-22
NAMEPLATEM-1	FIRE PREVENTION MEASURES	. S-23
FRAME PRODUCT IDENTIFICATION	EVACUATING IN CASE OF FIRE	. S-25
NUMBERM-2	BEWARE OF EXHAUST FUMES	. S-25
MTU DETROIT DIESEL DATA TAGM-2	PRECAUTIONS FOR WELDING,	
LEFT WHEEL MOTOR DATA TAGM-3	CUTTING, AND GRINDING	. S-26
RIGHT WHEEL MOTOR DATA TAG	REMOVE PAINT BEFORE WELDING	
LEFT SPINDLE ASSEMBLY DATA TAGM-3	OR CUTTING	. S-26
RIGHT SPINDLE ASSEMBLY DATA TAG M-3	AVOID HEATING NEAR PRESSURIZED	
TRACTION ALTERNATOR DATA TAGM-4	FLUID LINES	. S-27
TRACTION CONTROL CABINET	AVOID APPLYING HEAT TO LINES	
DATA TAGM-4	CONTAINING FLAMMABLE FLUIDS	. S-27
	PREVENT BATTERY EXPLOSIONS	. S-28
SAFETY	SERVICE AIR CONDITIONING	
	SYSTEM SAFELY	. S-38
RECOGNIZE SAFETY INFORMATION S-1	HANDLE CHEMICAL PRODUCTS SAFEL	
UNDERSTAND SIGNAL WORD	DISPOSE OF WASTE PROPERLY	
OPERATOR'S QUALIFICATIONS		
DUTIES OF THE OPERATOR	SAFETY SIGNS	
INSPECT RIGID DUMP TRUCK	FRONT VISIBILITY	00.5
FOLLOW SAFETY INSTRUCTIONS		
PREPARE FOR EMERGENCIES	SAFETY RADIATOR	
WEAR PROTECTIVE CLOTHING	NO JUMP START	
PROTECT AGAINST NOISES-4	FAN BLADE	
PROTECT AGAINST FLYING DEBRIS S-4	HIGH VOLTAGE	
GENERAL PRECAUTIONS FOR CAB S-5	TIRE SIZE	
USE HANDHOLDS AND STEPS	GROSS MACHINE WEIGHT	
ADJUST THE OPERATOR'S SEATS-6	RETARDER DECAL	. SS-6
FASTEN YOUR SEAT BELT S-7	FORWARD & REVERSE	
HANDLE STARTING AIDS SAFELY S-7	PROPULSION INHIBIT	. SS-7
OPERATE ONLY FROM OPERATOR'S	READ & UNDERSTAND	
SEATS-8	OPERATOR'S MANUAL	
JUMP STARTING S-8	HIGH PRESSURE	
KEEP RIDERS OFF RIGID DUMP TRUCK S-8	BODY DOWN	
PROTECT AGAINST FALLING STONES S-9	REAR VISIBILITY	
PROVIDE SIGNALS FOR JOBS S-9	BODY LOCK POSITION	
OPERATE THE RIGID DUMP	FOUR POINT LIFT	
TRUCK SAFELYS-10	NO TOWING	
AVOID INJURY FROM RUNNING OVER	OVERHEAD LOAD	
CRUSH AREAS-11	CRUSH AREA	. SS-9
AVOID TIPPINGS-12	BATTERY DISCONNECT	
AVOID INJURY FROM ROLLAWAY S-13	EMERGENCY SHUTDOWN	
NEVER TRAVEL WITH BODY OFF	PLANETARY LUBRICANT LEVEL	
THE FRAME S-13	MAINTENANCE FREE BATTERY	
OPERATING WITH THE RIGID DUMP	LOCK BODY	
TRUCK NEAR OVERHEAD WIRES S-14	CONTENTS UNDER PRESSURE	
OPERATING WITH THE RIGID DUMP	DO NOT LIFT	
TRUCK NEAR HIGH VOLTAGE	FASTEN THE SEAT BELT	
OVERHEAD POWER LINESS-14	AVOID EXHAUST FUMES	
PARK RIGID DUMP TRUCK SAFELY S-15	PEDAL LOCATION	SS-11
SAFE HANDLING OF OFF ROAD TIRES S-16	DISCHARGE ACCUMULATORS	SS-12

COMPONENTS NAME		LOAD DUMP BRAKE SWITCH	5-8
COMPONENTS NAME	1-1	OPERATING THE HOIST CONTROL	
		LEVER	5-9
ODEDATORIC CTATION		RIGID DUMP TRUCK STUCK IN DEEP	
OPERATOR'S STATION	0.4	SAND, SNOW OR MUD	5-13
DASH CONTROLS		COLD WEATHER RESTRICTIONS	5-13
LAMP DISPLAY		TOWING	
LCD MONITOR		PARKING RIGID DUMP TRUCK	
CONTROL, AC & HEATER			
STEERING COLUMN CONTROLS		TRANSPORTING THE RIGID DUM	D
FOOT CONTROLS			
CENTER CONSOLE CONTROLS		TRUCK	
OPERATOR'S SEAT ADJUSTMENT	2-51	TRANSPORTING	6-1
SEAT CONTROLS			
CAB REAR, COMPONENT LAYOUT	2-55	MAINTENANCE	
CAB OUTSIDE REAR PANEL	2-56	CORRECT MAINTENANCE AND	
REMOTE MOUNTED CONTROLS			7.4
HITACHI RIGID DUMP TRUCK		INSPECTION PROCEDURES	
PAYLOAD POLICY	2-60	WASHING RIGID DUMP TRUCK	/-1
HAUL CYCLE DATA		SERVICE RIGID DUMP TRUCK AT	
TAGE OT GEE DATA	2-02	SPECIFIED INTERVALS	
		RECOMMENDED LUBRICANTS	
BREAK-IN		RECOMMENDED FUEL	7-8
OBSERVE RIGID DUMP TRUCK		PREPARE RIGID DUMP TRUCK FOR	
CLOSELY	3-1	SERVICE	
		INSTALLING BODY PROP PINS	7-10
<b>OPERATING THE RIGID DUMP T</b>	BUCK	REMOVAL AND STORAGE OF	
INSPECT RIGID DUMP TRUCK	ROOK	BODY PROP PINS	7-11
DAILY BEFORE STARTING	4.4	ELECTRICAL DISCONNECTS BEFORE	
		WELDING ON THE RIGID DUMP	
PRE-OPERATION INSPECTION		TRUCK	7-12
OIL AND WATER LEAKS	4-4	MAINTENANCE INTERVAL GUIDE	
CHECK INSTRUMENTS & CONTROLS		A. GREASING	
BEFORE STARTING		B. ENGINE	
COOLANT LEVEL CHECK		C. POWER TRANSMISSION	
STARTING ENGINE		D. HYDRAULIC STEERING/BRAKE	
USING BOOSTER BATTERIES	4-9	APPLY SYSTEM	7 24
SUPPLEMENTAL STEER/BRAKE		E. HYDRAULIC HOIST/BRAKE	1-34
OPERATIONAL TEST	4-11	COOLING SYSTEM	7 40
LOADING			
LOAD WEIGHING	4-13	F. BRAKES, SERVICE AND PARK	
HAULING	4-17	G. FUEL SYSTEM	
DUMPING	4-18	H. AIR CLEANER	
STOPPING	4-21	I. COOLING SYSTEM	
ANTI-ROLL PROTECTION	4-21	J. ELECTRICAL SYSTEM	
STOPPING THE ENGINE	4-22	K. SUSPENSION, WHEELS AND TIRES	
	······ ==	L. CAB	
ODEDATING METHODS		M. GENERAL	7-89
OPERATING METHODS	_ ,	MAINTENANCE OF OPTIONAL	
GENERAL INFORMATION		SYSTEMS	7-93
COOLING A HOT ENGINE	5-2		
SHIFTING DIRECTIONAL RANGE		STORAGE	
SELECTOR		SHORT TERM STORAGE	Ω. 1
ACCELERATOR PEDAL		MODERATE TERM STORAGE	_
STEERING		LONG TERM STORAGE	
CRUISE CONTROL			
DYNAMIC RETARDER	5-4	RETURN TO SERVICE	გ-ნ
RETARDER DECAL	5-5		
SERVICE BRAKES			
PARK BRAKE			


TROUBLESHOOTING	
ENGINE	.9-1
ENGINE COOLING	.9-4
STARTER AND MOUNTING	.9-4
AIR CLEANER	.9-5
ELECTRICAL SYSTEM	.9-6
HYDRAULIC SYSTEM	
HYDRAULIC HOIST SYSTEM	
HYDRAULIC STEER SYSTEM	
STEER PUMP	9-13
STEER CONTROL VALVE	
FRONT AXLE	
REAR AXLE	
HOIST PUMP DRIVELINE	
REAR AXLE PLANETARY	
PARK BRAKE	<i>3</i> -19
SPECIFICATIONS	
SERVICE SPECIFICATIONS	
EH5000ACII	10-1
MACHINE DIMENSIONS	
PERFORMANCE/RETARDER CHARTS10	
OPTIONS	
OPTIONS	11-1
INFORMATION FEEDBACK FORM	
INFORMATION FEEDBACK FORM1	12-1
INDEX	
ALDHARETICAL INDEX	12 1

MEMO

The numbers asked for in this section are the individual numbers; model, product identification, serial, type and manufacturer given to each machine and major components. These numbers are requested when inquiring about replacement parts or machine service. Fill in the blank spaces in this section to immediately have them available upon request.

#### **MACHINE TYPE AND SERIAL NUMBER**

PRODUCT	
MODEL	
NUMBER:	
PRODUCT	
IDENTIFICATION	
NUMBER:	



EL20456


# ROLLOVER PROTECTIVE STRUCTURE NAMEPLATE

HITACHI
MODEL
TYPE:\_\_\_\_\_\_\_
ROPS
MODEL
NUMBER:\_\_\_\_\_\_
MAX
MACHINE
MASS, M-kg:




EL20475

# FRAME PRODUCT IDENTIFICATION NUMBER



EL2021

#### MTU DETROIT DIESEL DATA TAG




LEFT WHEEL MOTOR DATA TAG  TYPE:	Inside Axle
MFG. NO.:	
RIGHT WHEEL MOTOR DATA TAG	Inside Axle
TYPE:	
LEFT SPINDLE ASSEMBLY DATA TAG	
TYPE:	
RIGHT SPINDLE ASSEMBLY DATA TAG  TYPE:	Outside Flange

MFG. NO.:


#### TRACTION ALTERNATOR DATA TAG

TYPE:		
MEG NO ·		



# TRACTION CONTROL CABINET DATA TAG

TYPE:\_\_\_\_\_



#### RECOGNIZE SAFETY INFORMATION

#### • SAFETY ALERT SYMBOL

- This symbol, which will appear at various points in the manual and on the rigid dump truck together with a warning statement, means: "Warning, be alert! Your safety is involved!" Carefully read the message that follows. It is the obligation of the operator to make sure that all warning decals are in place on the rigid dump truck and that they are readable. Accidents may otherwise occur.
- Follow recommended precautions and safe operating practices.
- Every country (Jurisdiction) has its own safety regulations. It is the obligation of the operator to know and follow these. This also applies to local regulations covering different types of work. Should the recommendations in this manual deviate from those of your country (Jurisdiction), your local safety regulations should be followed.



#### **UNDERSTAND SIGNAL WORD**

- On the rigid dump truck safety signs, signal words designating the degree or level of hazard – DANGER, WARNING, or CAUTION – are used with the safety alert symbol.
  - DANGER indicates an imminently hazardous situation which, if not avoided, will result in death or serious injury.
  - WARNING indicates a potential hazardous situation which, if not avoided, could result in death or serious injury.
  - CAUTION indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury.
  - DANGER or WARNING safety signs are located near specific hazards. General precautions are listed on CAUTION safety signs.
- These signal words also call attention to safety messages in this manual.
- To avoid confusing rigid dump truck protection with personal safety messages, a signal word IMPORTANT indicates a situation which, if not avoided, could result in damage to the rigid dump truck.
  - NOTE: indicates an additional explanation for an element of information.



#### **OPERATOR'S QUALIFICATIONS**

- Only trained personnel should operate the rigid dump truck.
- Operator should be of legal rigid dump truck operating age according to country (Jurisdiction) regulations and familiar with the operation and maintenance of the rigid dump truck.
- Operator must be licensed if required by National Rules and Regulations.

#### **DUTIES OF THE OPERATOR**

- Before you operating the rigid dump truck, this manual must be read and understood. Contact your supervisor if you do not understand any portion of this manual. By reading and understanding the manual, you will become aware of and observe how to avoid injury and damage.
- Know the work area and the company rules and regulations
- Never operate the rigid dump truck while under the influence of alcohol, medicine or other drugs.

Due to the position of the cab and size of the rigid hauler, the operator has limited visibility to areas close to or near the rigid dump truck. No person should enter the operating area of the rigid dump truck when it is in operation without first notifying the operator. If a person has to enter the operating area of the rigid dump truck, they should signal the operator and wait for an acknowledgement of recognition by the operator.

During rigid dump truck operation no one should be allowed to get any closer than 7m (23 ft.) of the rigid dump truck. Any closer will limit one's time to react and move away from the vehicle when it starts.

#### INSPECT RIGID DUMP TRUCK

- Inspect your rigid dump truck carefully each day or shift by walking around it before you start it to avoid personal injury.
  - Be sure to cover all points described under "Pre-Operation Inspection" found in the OPERATING THE RIGID DUMP TRUCK section in this operator's manual.



SA-435

#### **FOLLOW SAFETY INSTRUCTIONS**

- · Carefully read and follow all safety signs on the rigid dump truck and all safety messages in this manual.
- Safety signs should be installed, maintained and replaced when necessary.
  - · If a safety sign or this manual is damaged or missing, order a replacement from your authorized Hitachi dealer in the same way you order other replacement parts (be sure to state rigid dump truck model and serial number when ordering).
- Learn how to operate the rigid dump truck and its controls correctly and safely.
- · Allow only trained qualified, authorized personnel to operate the rigid dump truck.
- Keep your rigid dump truck in proper working condition.
  - · Unauthorized modifications of the rigid dump truck may impair its function and/or safety and affect rigid dump truck life.
- The safety messages in this SAFETY chapter are intended to illustrate basic safety procedures of rigid dump trucks. However it is impossible for these safety messages to cover every hazardous situation you may encounter. If you have any questions, you should first consult your supervisor and/or your authorized Hitachi dealer before operating or performing maintenance work on the rigid dump truck.



#### PREPARE FOR EMERGENCIES

- Be prepared if a fire starts or if an accident occurs.
  - · It is recommended that a first aid kit and fire extinguisher be kept on hand.
  - · Thoroughly read and understand the label attached on the fire extinguisher to use it properly.
  - To ensure that a fire extinguisher can be always used when necessary, check and service the fire extinguisher at the recommended intervals as specified in the fire-extinguisher manual.
  - · Establish emergency procedure guidelines to cope with fires and accidents.
  - · Keep emergency numbers for doctors, ambulance service, hospital, and fire department posted near your telephone.



SA-437

#### WEAR PROTECTIVE CLOTHING

• Wear close fitting clothing and personal protective safety equipment (PPE) appropriate to the job.

You may need:

A hard hat

Safety shoes

Safety glasses, goggles, or face shield

Heavy gloves

Hearing protection

Reflective clothing

Wet weather gear

Respirator or filter mask.

Be sure to wear the correct equipment and clothing for the job. Do not take any chances.

- Avoid wearing loose clothing, jewelry, or other items that can catch on control levers or other parts of the rigid dump truck.
- Operating equipment safely requires the full attention of the operator. Do not wear radio or music headphones while operating the rigid dump truck.



SA-438

#### **PROTECT AGAINST NOISE**

- Prolonged exposure to loud noise can cause impairment or loss of hearing.
  - Wear a suitable hearing protective device such as ear muffs or ear plugs to protect against objectionable or uncomfortably loud noises. This may be necessary when working outside of the cab during the Pre-Operation Inspection, for example.



SA-434

#### PROTECT AGAINST FLYING DEBRIS

- If flying debris hit eyes or any other part of the body, serious injury may result.
  - Guard against injury from flying pieces of metal or debris; wear goggles or safety glasses.



SA-432

Thank you so much for reading. Please click the "Buy Now!" button below to download the complete manual.



After you pay.

You can download the most perfect and complete manual in the world immediately.

Our support email: ebooklibonline@outlook.com