

SERVICEMAN HANDBOOK

MINI-EXCAVATOR

SR-3 SERIES

1. MACHII	NE SPECIFICATIONS	
1.1 GEI	NERAL DIMENSIONS	1-2
1.1.1	CANOPY	1-2
1.1.2	CANOPY	
	CAB	
	CAB	
	ECIFICATIONS AND PERFORMANCE	
1.3 ENG	GINE SPECIFICATIONS	1-16
1.3.1	SPECIFICATIONS	1-16
1.3.2	ENGINE PERFORMANCE CURVE	
1.3.3	SPECIFICATIONS	1-18
1.3.4	ENGINE PERFORMANCE CURVE	
1.3.5 1.3.6	ENGINE PERFORMANCE CURVE	
1.3.7	SPECIFICATIONS	
1.3.8	ENGINE PERFORMANCE CURVE	
1.4 HYI	DRAULIC COMPONENTS	1-24
1.4.1	SPECIFICATIONS	
1.4.2	SPECIFICATIONS	
1.4.3	SPECIFICATIONS	
1.4.4	SPECIFICATIONS	1-30
1.5 MA	CHINE & COMPONENTS WEIGHT	1-32
1.6 WO	RKING RANGES	1-39
1.6.1	CANOPY TYPE	1-39
1.6.2	CANOPY TYPE	
1.6.3	CAB TYPE	
1.6.4	CANOPY TYPE	
1.6.5 1.6.6	CANOPY TYPE	
1.6.7	CANOPT TIPE	
	CANOPY TYPE	
	CAB TYPE	
	CANOPY TYPE	
	CAB TYPE	
	CANOPY TYPE	
	TING DIAGRAM	
1.8 PEF	RFORMANCE TABLE	1-64
2. MAINTE	ENANCE	
	SIGNATED OIL AND GREASE, AND FILTER ELEMENT	
	GREASE AND OIL LIST	
	GREASE AND OIL LIST	
2.1.3 2.1.4	GREASE AND OIL LIST	2-4 2-5
2.1.4	FILTERS & ELEMENTS, AND BUCKET	2-6
	FILTEDO & ELEMENTO, AND DICKET	

	FILTERS & ELEMENTS, AND BUCKET	2-8
2.2 MA	INTENANCE STANDARDS AND TEST PROCEDURES	2-10
2.2.1	STANDARD VALUE TABLE	
2.2.2	STANDARD VALUE TABLE	2-12
2.2.3	STANDARD VALUE TABLE	2-14
2.2.4	STANDARD VALUE TABLE	2-16
2.2.5	MEASURING ENGINE SPEED	
2.2.6	MEASURING HYDRAULIC OIL PRESSURE	2-23
2.2.7	MEASURING TRAVEL PERFORMANCES (ALL MODELS)	
2.2.8	MEASURING SLEW PERFORMANCES (ALL MODELS)	
2.2.9	MEASURING ATTACHMENT OPERATING PERFORMANCES	2 00
	(ALL MODELS)	2-41
2.2.10	MEASURING SLEW BEARING PERFORMANCES	
2.2.10	(ALL MODELS)	2-43
2 2 11	MEASURING CRAWLER TENSION (ALL MODELS)	2-44
	· · · · · · · · · · · · · · · · · · ·	
2.3 AT	FACHMENT MAINTENANCE STANDARD	2-46
2.3.1	CLEARANCE OF PIN AND BUSHING	2-46
2.3.2	CLEARANCE IN THRUST DIRECTION ON BOOM AND	
	CYLINDER INSTALLATION SECTION	2-57
2.3.3	CLEARANCE IN THRUST DIRECTION ON ARM AND	
	CYLINDER INSTALLATION SECTION	2-60
2.3.4	CLEARANCE IN THRUST DIRECTION ON THE DOZER	
	CLEARANCE IN THRUST DIRECTION ON THE DOZER AND CYLINDER INSTALLATION SECTION	2-65
2.3.5	CLEARANCE IN THRUST DIRECTION ON SWING BRACKET AND CY	
	INSTALLATION SECTION	
24 UN	DERCARRIAGE	
2.4.1	RUBBER CRAWLER	
2.4.2	STEEL CRAWLER (SK17SR-3, CX17B, E18SR, SK15SR-3)	2-72
2.4.3	STEEL CRAWLER	
	(SK20SR-3 / SK27SR-3, CX27B, E27SR / SK30SR-3, CX31B, E30SR / SK20SR-3, CX31B, E30SR / SK20SR / SK20SR-3, CX31B, E30SR / SK20SR	
	OVOOD FORODY	
	CX36B, E35SR)	
2.4.4	STEEL CRAWLER	2-73
	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR , SK55SR-3, CX55B)	2-73
2.4.42.4.5	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR , SK55SR-3, CX55B) UPPER ROLLER	2-73 2-74
	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B) UPPER ROLLER (SK20SR-3 / SK27SR-3, CX27B, E27SR / SK30SR-3, CX31B, E30SR / SK20SR-3, CX31B, E30SR / SK20SR / SK20SR-3, CX31B, E30SR / SK20SR /	2-73 2-74 SK35SR-3,
2.4.5	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B) UPPER ROLLER (SK20SR-3 / SK27SR-3, CX27B, E27SR / SK30SR-3, CX31B, E30SR / CX36B, E35SR)	2-73 2-74 SK35SR-3,
	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-75
2.4.5	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-75
2.4.5 2.4.6 2.4.7	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-75
2.4.5	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-75 2-76 2-77
2.4.5 2.4.6 2.4.7	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR , SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-75 2-76 2-77 SK35SR-3,
2.4.5 2.4.6 2.4.7	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-75 2-76 2-77 SK35SR-3,
2.4.5 2.4.6 2.4.7	STEEL CRAWLÉR (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-75 2-76 2-77 SK35SR-3, 2-78
2.4.5 2.4.6 2.4.7 2.4.8	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-75 2-76 2-77 SK35SR-3, 2-78
2.4.5 2.4.6 2.4.7 2.4.8	STEEL CRAWLÉR (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-75 2-76 2-77 SK35SR-3, 2-78
2.4.5 2.4.6 2.4.7 2.4.8 2.4.9 2.4.10	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR, SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-76 2-77 SK35SR-3, 2-78 2-79
2.4.5 2.4.6 2.4.7 2.4.8 2.4.9 2.4.10 2.4.11	STEEL CRAWLER (SK40SR-3 / SK50SR-3, CX50B, E50SR , SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-76 2-77 SK35SR-3, 2-78 2-79
2.4.5 2.4.6 2.4.7 2.4.8 2.4.9 2.4.10 2.4.11	STEEL CRAWLÉR (SK40SR-3 / SK50SR-3, CX50B, E50SR , SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-76 2-77 SK35SR-3, 2-78 2-79 2-80 2-81
2.4.5 2.4.6 2.4.7 2.4.8 2.4.9 2.4.10 2.4.11 2.4.12	STEEL CRAWLÉR (SK40SR-3 / SK50SR-3, CX50B, E50SR , SK55SR-3, CX55B)	2-73 2-74 SK35SR-3, 2-76 2-77 SK35SR-3, 2-78 2-79 2-80 2-81

2.4.15	IDLER ADJUSTER (SK20SR-3 / SK27SR-3, CX27B, E27SR)	2 0 4
2.4.16	6 IDLER ADJUSTER	2-04
2	(SK30SR-3, CX31B, E30SR / SK35SR-3, CX36B, E35SR)	2-85
2.4.17	IDLER ADJUSTER	
	(SK40SR-3 / SK50SR-3, CX50B, E50SR , SK55SR-3, CX55B)	
2.4.18	SPROCKET	2-86
3. CIRCU	IT DIAGRAM	
3.1 HY	DRAULIC CIRCUITS	3-2
3.1.1	STANDARD	3-2
3.1.2	STANDARD	
3.1.3	STANDARD	3-6
3.1.4	STANDARD	3-12
3.1.5	STANDARD	3-14
3.1.6	STANDARD	
3.1.7	STANDARD	
3.1.8	STANDARD	
3.1.9	STANDARD	
	STANDARD	
	STANDARD	
	STANDARD	
3.2 ELI	ECTRIC CIRCUIT DIAGRAM	3-30
4. ATTAC	HMENT DIMENSIONS	
4.1 BO	OM	4-2
4.1.1	BOOM DIMENSIONAL DRAWING	4-2
	M	
	ARM DIMENSIONAL DRAWING	
	CKET	
4.3.1	BUCKET DIMENSIONAL DRAWING	4- 6
	LUG SECTION DIMENSIONAL DRAWING	
4.3.3	BOSS SECTION DIMENSIONAL DRAWING	4-9
4.4 DO	ZER	4-10
4.4.1	DOZER DIMENSIONAL DRAWING	. 4-10
4.4.2	DOZER DIMENSIONAL DRAWING	.4-12
4.5 SW	/ING	. 4-14
4.5.1	SWING BRACKET DIMENSIONAL DRAWING	. 4-14
	LINDER	
4.6.1	HYDRAULIC CYLINDER	
	APE AND DIMENSIONS OF PIN	
	SHAPE OF PIN	
	DIMENCIANC ACDIN	1 22
	DIMENSIONS OF PIN	-
4.8 SH	APE AND DIMENSIONS OF BUSHING	-

4.8.2	DIMENSIONS OF BUSHING4-2	8
5. DIFFER	RENTIAL MATERIAL	
5.1 TO	RQUE SPECIFICATIONS FOR CAPSCREWS & NUTS5	-2
5.1.1	Metric Coarse Thread Standard Tightening Torque Values. Make Certain to tighten all Capscrews & Nuts to proper torque values. 5-	0
5.1.2	Metric Fine Thread Standard Tightening Torque values. Make certain to tighten all Capscrews & Nuts to proper torque values. 5-	
5.2 SC	REW AND TOOL SIZES	
5.2.1	Capscrew	4
5.3 TO	RQUE SPECIFICATIONS FOR JOINTS AND HOSES5-	4
5.3.1 5.3.2	JOINTS FOR PIPING (O-RING SEALING TYPE)5- HYDRAULIC HOSE (30° FLARE TYPE)5-	
	RQUE SPECIFICATIONS FOR SLEEVE TYPE TUBE	
	TINGS	
	SLEEVE TYPE TUBE FITTINGS5- PART NO5-	
	UGS5-	
5.5.1	Plug for hydraulic pipe joint5-	
5.5.2	Plug for hydraulic equipment5-	
	ECIAL SPANNERS FOR TUBES5-	
	ECIAL TOOLS5-	8
	PLICATION OF SCREW LOCKING AND SEALING MPOUNDS5-	Ω
	UNTERWEIGHT LIFTING JIG5-	
	PER FRAME LIFTING JIG5-	
	FERENTIAL TABLE5-	
	INTERNATIONAL UNIT	
	CONVERSION TABLE	
5.12 INC	CLINE CONVERSION TABLE5-	19
Note		
• • • • • • • • • • • • • • • • • • • •	nodel: Similar model	
	-3: CX17B, E18SR, SK15SR-3	
 SK20SR- SK27SR- 	-3: CX27B, E27SR	
	3: CX31B, E30SR	
	3: CX36B, E35SR	
• SK40SR-	3	
SK50SR-	3: CX50B, E50SR , SK55SR-3, CX55B	

Thank you so much for reading.

Please click the "Buy Now!"

button below to download the complete manual.



After you pay.

You can download the most perfect and complete manual in the world immediately.

Our support email: ebooklibonline@outlook.com