14PZ and 14SZ 21-Inch Walk-Behind Rotary Mowers (Serial No. 010001—)

John Deere Horicon Works
OMM95319 Issue H2
(This manual replaces OMM95319 L0.)
LITHO IN U.S.A.
ENGLISH

Introduction

THANK YOU for purchasing a John Deere product.

READ THIS MANUAL to learn how to operate and service your mower. Failure to do so could result in personal injury or equipment damage.

RIGHT AND LEFT SIDES are determined by facing the direction of forward travel.


DEALER NAME	
PHONE NUMBER	
DATE OF PURCHASE	

WARRANTY IS EXPLAINED on the warranty certificate you received from your dealer. Please read it

WRITE MACHINE NUMBERS BELOW. You need these numbers to help you order parts and to help trace the mower if it is stolen. Also record these numbers in a safe place in case the manual is lost.

 A—Mower 	Model
• B—Mower	Number
• C—Engine	Number





SERVICE SCHEDULE

Before Use: Check oil level.

First 5 Hours: Change engine oil.

25 Hours:

- -Clean air cleaner element.
- —Tighten blade bolt.
- —Lubricate rear axle bushings.
- -Clean & gap spark plug.
- —Clean 14SZ belt area.
- -Change engine oil.

250 Hours: Have John Deere dealer check flywheel brake liner.

AS NECESSARY

- -Adjust 14SZ traction cable.
- —Clean fins.
- —Adjust throttle cable.
- -Adjust slow idle.
- -Check, remove, & sharpen blade.
- -Balance & install blade.
- —Clean fuel cap vents.

PART NUMBERS are subject to change without notice, & may be different outside the U.S.A.

- -Air cleaner element: AM116236
- -Belt: M77167
- —Standard blade: M111453 —Mulching blade: M112972 —Spark plug: Champion RCJ8

MX,IFC,95319 -19-14JUL92

Contents

Page		
Safety 1 Operating Engine & Mower Controls 5 Controls 5 Start Engine 5 Stop Engine 6 Adjust Cutting Height 7 Adjust Handle Height 7 14SZ Forward Travel 8 14SZ Travel Speeds 8 Transport Mower 8	Service—Blade Check/Tighten/Remove Blade	
Mowing, Bagging, & Mulching Mowing Tips 9 Discharge Chute 10 Bagging Tips 10 Grass Bag 11 Mulching Tips 12 Mulch Blade 13 Mulch Plug 13 Troubleshooting 14		
Service—Miscellaneous 15 Lubricate Rear Axle Bushings 15 Clean 14SZ Belt Area 15 Adjust 14SZ Traction Clutch 16 Service—Engine Handle Fuel Safely 17 Fuel and Oil 17 Check Engine Oil Level 18		
Change Engine Oil19Clean Air Cleaner Element20Clean & Gap Spark Plug20Adjust Throttle Cable21Adjust Slow Idle21Clean Fuel Cap Vents22Clean Fins22		

All information, illustrations and specifications in this manual are based on the latest information available at the time of publication. The right is reserved to make changes at any time without notice.

OMM95319 H2-19-07JUL92

COPYRIGHT® 1992
DEERE & COMPANY
Moline, Illinois
All rights reserved
A John Deere ILLUSTRUCTION™ Manual
Previous Editions
Copyright 1991 & 1990 Deere & Company

Page

... 23

. . . 24

. . . 26

. . . 28

Safety

READ SAFETY SIGNS & INSTRUCTIONS



This symbol means **BE ALERT FOR POSSIBLE INJURY**.

DANGER points out immediate hazards which will cause severe injury or death.

WARNING points out hazards or unsafe practices which could cause severe injury or death.

CAUTION points out hazards or unsafe practices which could cause minor injury or machine or property damage.

KEEP SAFETY SIGNS in good condition. You can order safety signs from your John Deere dealer.

READ THIS MANUAL CAREFULLY. Be thoroughly familiar with controls and proper use of equipment.

ALLOW ONLY RESPONSIBLE ADULTS, who understand instructions, to operate the machine.

IF YOU DON'T UNDERSTAND any part of this manual, see your John Deere dealer.



Left Side of Deck



Right Side of Deck

M73149

-19-23FEB90



- Pick up objects that blade may hit and throw
- Keep children and bystanders far away
 Stop engine before adjusting cutting height
 Read operator's manual

Top, Rear of Engine



A DANGER

ROTATING BLADE
Stop engine before lifting door and clearing discharge
THROWN OBJECTS
Do not lift or block door open with blade engaged

Do not mow without catcher, side chute or mulcher plug/plate in place

19-02JAN91

Rear of Door

MX,SAFW,A

-19-14JUL92



PREPARE BEFORE YOU OPERATE

Check hardware often, especially blade and engine mounting bolts. Keep them tight.

Discharge chute, grass bag, or mulch plug must be in good condition, held in place by door.

To help prevent fires, keep engine clean, especially cooling fins. Replace faulty muffler.

Wear close-fitting clothing, substantial footwear—not barefoot or sandals—and long trousers.

Protect eyes with shield, safety glasses, or goggles.

Protect ears with earplugs or ear muffs.

Focus on mowing. Don't wear headphones.

Be prepared for fire. Keep fire extinguisher and first aid kit handy. Keep medical and fire department emergency numbers near telephone.

MX,SAFW,C

-19-14JUL92


PROTECT AGAINST THROWN OBJECTS

Don't mow when people are in mowing area.

Before you mow, clear area of objects that might be thrown by blade: sticks, rocks, bones, wire, etc.

Discharge clippings away from people.

Don't lift or block discharge door open when blade is ENGAGED.




PROTECT CHILDREN

KEEP CHILDREN IN HOUSE WHILE YOU MOW. If children come into mowing area, STOP MOWER. Move children to a safe place. Also keep other people and pets out of mowing area.

Don't let children or untrained persons operate mower.

Don't leave mower unattended with engine running.



Thank you so much for reading. Please click the "Buy Now!" button below to download the complete manual.



After you pay.

You can download the most perfect and complete manual in the world immediately.

Our support email: ebooklibonline@outlook.com