

350 and 450 Mowers

(Serial No. 800001-)

John Deere Ottumwa Works
OME87606 Issue G5
(This manual replaces OME82271 D2)

LITHO IN U.S.A.
ENGLISH

IDENTIFICATION VIEWS



E22722 -UN-13MAR89

Right Rear View of John Deere 350 Mower



E26730 -UN-13MAR89

Left Rear View of John Deere 450 Mower

DELIVERY

The following checklist is a reminder of very important information which should be conveyed directly to the customer at the time the mower is delivered. Check off each item as it is fully explained.

- | | |
|--|--|
| <ul style="list-style-type: none"> <input type="checkbox"/> Advise customer that life expectancy of this machine like any other machine, is dependent upon regular lubrication as described in the operator's manual. <input type="checkbox"/> Give operator's manual to the customer and explain all operating adjustments and lubrication fully. <input type="checkbox"/> Explain proper hookup of hydraulic cylinder advising that hydraulic hoses must be 9-1/2 ft (2.90 m) long. | <ul style="list-style-type: none"> <input type="checkbox"/> Explain proper ASAE standard dimensions for PTO hookup. <input type="checkbox"/> Advise customer of safety precautions that must be observed while using this mower. <input type="checkbox"/> Advise customer of the optional attachments that are available for special crop and operating conditions. <input type="checkbox"/> When mower is transported on a road or highway at night or during the day, accessory lights and devices should be used for adequate warning to operators of other vehicles. Various safety lights and devices are available from your John Deere dealer. In this regard, tell the customer to check local governmental regulations. |
|--|--|

(Date Delivered)

(Signature)

EX,450U,C -19-07APR92

AFTER SALE

It is suggested the following items be checked sometime during the first season's operation.

- | | |
|---|--|
| <ul style="list-style-type: none"> <input type="checkbox"/> Go over entire machine for loose or missing hardware. <input type="checkbox"/> Check for broken or damaged parts. <input type="checkbox"/> All shields are in place. | <ul style="list-style-type: none"> <input type="checkbox"/> Check operating adjustments. <input type="checkbox"/> If possible, run mower to see if it is functioning properly. <input type="checkbox"/> Review the entire operator's manual with the customer and stress the importance of proper and regular lubrication and safety precautions. |
|---|--|

(Date Checked)

(Signature)

EX,450U,D -19-07APR92

Contents

	Page		Page
Safety	1	Every 50 Hours	35
Preparing the Tractor for 350 Mower	11	Troubleshooting	37
Preparing the Tractor for 450 Mower	13	Service	
Preparing the Mower	14	Practice Safety	40
Attaching and Detaching		Adjusting Grass Divider and Arm	40
Attaching 350 Mower to Tractor	17	Aligning Knife and Outer Shoe Stripper Plate	41
Removing 350 Mower from Tractor	18	Adjusting Subsoles	41
Attaching 450 Mower to Tractor	19	Adjusting Cutterbar Tilt	42
Attaching PTO POWER-GARD Driveline	19	Adjusting Cutterbar Lead	42
Attaching Hydraulic Cylinder	20	Adjusting Outer Shoe Lift	43
Checking Hydraulic System	20	Adjusting Inner Shoe Float 350 Mower	44
Removing 450 Mower from Tractor	21	450 Mower	45
Detaching PTO POWER-GARD Driveline	22	Adjusting Outer Shoe Float	46
Transporting	23	Adjusting Drive Belt	47
Operating the Mower		Checking Standard Cutterbar	47
Breaking in the New Mower	25	Aligning Guards	48
Changing From Transport Position To Operating Position	26	Replacing Innermost Guard	48
Operating Speed	27	Replacing Guard Plates	49
Turning Corners	27	Adjusting Wear Plates	49
Cutterbar Release Latch		Adjusting Knife Hold-Down	50
Resetting	28	Taking Care of the Knife	50
Adjusting	28	Installing Non-Clog Cutterbar Parts	50
Removing Debris on Cutterbar	28	Adjusting Non-Clog Knife Hold-Downs	52
Checking Cutterbar	29	Adjusting Wear Plates	53
Attachments	30	Knife Sections	
Lubrication and Maintenance		Sharpening	54
Perform Lubrication and Maintenance	33	Replacing	54
Grease	33	Removing Cutterbar Knife	54
As Required	34	Replacing Knife Head Bearing and Seal (If Equipped)	55
Every 10 Hours	34	Installing and Adjusting Knife Pin (If Equipped)	55
		Replacing Knife Head Bearing (If Equipped)	56
		Installing Snap-In Guard	56
		Replacing Plate on Outer Shoe	57

Continued on next page

All information, illustrations and specifications in this manual are based on the latest information available at the time of publication. The right is reserved to make changes at any time without notice.

OME87606 G5-19-14JUL95

COPYRIGHT© 1995
DEERE & COMPANY
Moline, Illinois
All rights reserved
A John Deere ILLUSTRATION™ Manual
Previous Editions
Copyright 1992, 1989, 1985 Deere & Company

Contents

	Page
Storage	58
Assembly—350 Mower	59
Assembly—450 Mower	66
Specifications	
Machine Specifications	73
Serial Number	74
Bolt and Cap Screw Torque Value Charts	
Inch	75
Metric	76
Crime Prevention Tips	77
Index	

Safety

RECOGNIZE SAFETY INFORMATION

This is the safety-alert symbol. When you see this symbol on your machine or in this manual, be alert to the potential for personal injury.

Follow recommended precautions and safe operating practices.



DX,ALERT -19-03MAR93

T81389 -UN-07DEC68

UNDERSTAND SIGNAL WORDS

A signal word—DANGER, WARNING, or CAUTION—is used with the safety-alert symbol. DANGER identifies the most serious hazards.

DANGER or WARNING safety signs are located near specific hazards. General precautions are listed on CAUTION safety signs. CAUTION also calls attention to safety messages in this manual.



DX,SIGNAL -19-03MAR93

TS187 -19-30SEP88


FOLLOW SAFETY INSTRUCTIONS

Carefully read all safety messages in this manual and on your machine safety signs. Keep safety signs in good condition. Replace missing or damaged safety signs. Be sure new equipment components and repair parts include the current safety signs. Replacement safety signs are available from your John Deere dealer.

Learn how to operate the machine and how to use controls properly. Do not let anyone operate without instruction.

Keep your machine in proper working condition. Unauthorized modifications to the machine may impair the function and/or safety and affect machine life.

If you do not understand any part of this manual and need assistance, contact your John Deere dealer.



DX,READ -19-03MAR93

TS201 -UN-23AUG88



PROTECT BYSTANDERS

Stand clear of mower at all times when machine is operating and when raising and lowering cutterbar.

Do not allow children to operate tractor or mower.



EX,450C,A -19-08FEB89

TS255 -UN-23AUG88

OPERATE MOWER SAFELY

Check hardware, condition of hydraulic hoses and connections, and machine condition before operating.

All safety shields must be in place.


Slow down on hillsides and curves to minimize the danger of tipping. Do not mow near the edge of a ditch or gully.

EX,450C,B -19-08FEB89

KEEP RIDERS OFF MACHINE

Only allow the operator on the machine. Keep riders off.

Riders on machine are subject to injury such as being struck by foreign objects and being thrown off of the machine. Riders also obstruct the operator's view resulting in the machine being operated in an unsafe manner.



DX,RIDER -19-03MAR93


TS290 -UN-23AUG88

PREPARE FOR EMERGENCIES

Be prepared if a fire starts.

Keep a first aid kit and fire extinguisher handy.

Keep emergency numbers for doctors, ambulance service, hospital, and fire department near your telephone.



DX,FIRE2 -19-03MAR93

TS291 -UN-23AUG88




WEAR PROTECTIVE CLOTHING

Wear close fitting clothing and safety equipment appropriate to the job.

Prolonged exposure to loud noise can cause impairment or loss of hearing.

Wear a suitable hearing protective device such as earmuffs or earplugs to protect against objectionable or uncomfortable loud noises.

Operating equipment safely requires the full attention of the operator. Do not wear radio or music headphones while operating machine.



DX,WEAR -19-10SEP90

TS206 -UN-23AUG68


HANDLE CHEMICAL PRODUCTS SAFELY

Direct exposure to hazardous chemicals can cause serious injury. Potentially hazardous chemicals used with John Deere equipment include such items as lubricants, coolants, paints, and adhesives.

A Material Safety Data Sheet (MSDS) provides specific details on chemical products: physical and health hazards, safety procedures, and emergency response techniques.

Check the MSDS before you start any job using a hazardous chemical. That way you will know exactly what the risks are and how to do the job safely. Then follow procedures and recommended equipment.

(See your John Deere dealer for MSDS's on chemical products used with John Deere equipment.)



DX,MSDS,NA -19-03MAR93

TS1132 -UN-26NOV90



STAY CLEAR OF ROTATING DRIVELINES

Entanglement in rotating driveline can cause serious injury or death.

Keep tractor master shield and driveline shields in place at all times. Make sure rotating shields turn freely.

Wear close fitting clothing. Stop the engine and be sure PTO driveline is stopped before making adjustments, connections, or cleaning out PTO driven equipment.



DX.PTO -19-03MAR93


TS198 -UN-23AUG88

USE SAFETY LIGHTS AND DEVICES

Slow moving tractors, self-propelled equipment and towed implements or attachments can create a hazard when driven on public roads. They are difficult to see, especially at night. Avoid personal injury or death resulting from collision with a vehicle.

Whenever driving on public roads, use flashing warning lights and turn signal according to local regulation. To increase visibility, use the lights and devices provided with your machine. For some equipment, install extra flashing warning lights.

Keep safety items in good condition. Replace missing or damaged items. An implement safety lighting kit is available from your John Deere dealer.



DX.FLASH -19-15MAR93


TS951 -UN-12APR90

USE A SAFETY CHAIN

A safety chain will help control drawn equipment should it accidentally separate from the drawbar.

Using the appropriate adapter parts, attach the chain to the tractor drawbar support or other specified anchor location. Provide only enough slack in the chain to permit turning.

See your John Deere dealer for a chain with a strength rating equal to or greater than the gross weight of the towed machine. Do not use safety chain for towing.



DX.CHAIN -19-03MAR93

TS217 -UN-23AUG88

Thank you so much for reading.
Please click the “Buy Now!”
button below to download the
complete manual.



After you pay.

You can download the most
perfect and complete manual in
the world immediately.

Our support email:

ebooklibonline@outlook.com